

DURATION



CATÁLOGO DE PRODUCTO

DURATION



FM-22

- Sound water-evacuation and skidding-resistance capability.
- Soundly resistance irregular wear.

SIZE	LOAD INDEX	SPEED SYMBOLS	DEPTH (mm)	STANDARD RIM	MAX LOAD AND INFLATED PRESSURE				SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	WEIGHT (kg)
					DUAL		SINGLE				
					KG	KPA	KG	KPA			
11R22.5	146/143	M	15.0	7.50,8.25	2725	830	3000	830	279	1054	51.80
11R24.5	149/146	M	15.0	7.50,8.25	3000	830	3250	830	279	1104	55.60
295/75R22.5	146/143	M	15.0	8.25,9.00	3000	830	2725	830	298	1014	50.65



FM-71

- Sounds bearing, braking and driving capability.

SIZE	LOAD INDEX	SPEED SYMBOLS	DEPTH (mm)	STANDARD RIM	MAX LOAD AND INFLATED PRESSURE				SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	WEIGHT (kg)
					DUAL		SINGLE				
					KG	KPA	KG	KPA			
11R22.5	146/143	M	15.0	7.50,8.25	2725	830	3000	830	279	1054	51.80
11R24.5	149/146	M	15.0	7.50,8.25	3000	830	3250	830	279	1104	55.60



FM-04

- Suitable for good road surface application.
- With excellent anti-side-skid character, low rolling resistance.
- Low heat generating, excellent high-speed driving character.

SIZE	LOAD INDEX	SPEED SYMBOLS	DEPTH (mm)	STANDARD RIM	MAX LOAD AND INFLATED PRESSURE				SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	WEIGHT (kg)
					DUAL		SINGLE				
					KG	KPA	KG	KPA			
11R22.5	146/143	L	21.0	7.50,8.25	2725	930	3000	930	279	1065	54.60
11R24.5	149/146	L	21.0	7.50,8.25	3000	830	3250	830	279	1116	58.60
295/75R22.5	146/143	L	21.0	8.25,9.00	3000	830	2725	830	298	1020	52.80